



Trade name: Marabu-Porcelain 555, 15 ml Marabu-Porcelain 555, 15 ml

Version: 4 / GB

Date revised: 17.12.2015

Substance number: 110539555

Replaces Version: 3 / GB

Print date: 17.12.15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Marabu-Porcelain 555, 15 ml Marabu-Porcelain 555, 15 ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/preparation

Paint

Identified Uses

SU3

Industrial uses: Uses of substances as such or in preparations at industrial sites

PC9a

Coatings and paints, thinners, paint removers

1.3. Details of the supplier of the safety data sheet

Address

Marabu GmbH & Co. KG

Asperger Strasse 4

71732 Tamm

Germany

Telephone no. +49-7141/691-0

Fax no. +49-7141/691-147

Information provided Department product safety

by / telephone

E-mail address of PRSI@marabu.de

person responsible

for this SDS

1.4. Emergency telephone number

(+49) (0)621-60-43333

SECTION 2: Hazards identification ***

2.1. Classification of the substance or mixture

This product is not classified hazardous in accordance with Regulation (EC) No 1272/2008.

2.2. Label elements

Labelling according to regulation (EC) No 1272/2008

Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

EUH208 Contains A mixture of: 5-Chloro-2-methyl-2h-isothiazol-3-one [EC-no. 247-500-7] and 2-Methyl-2H-isothiazol-3-one [EC-no. 220-239-6] (3:1), 1,2-Benzisothiazol-3(2h)-one, May produce an allergic reaction.

Supplemental information

EUH205

Contains epoxy constituents. May produce an allergic reaction.

2.3. Other hazards

No special hazards have to be mentioned.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Paint based on acrylic resins and on water



Trade name: Marabu-Porcelain 555, 15 ml Marabu-Porcelain 555, 15 ml

Version: 4 / GB

Date revised: 17.12.2015

Substance number: 110539555

Replaces Version: 3 / GB

Print date: 17.12.15

Hazardous ingredients**3-Butoxypropan-2-ol**

CAS No.	5131-66-8				
EINECS no.	225-878-4				
Concentration	>=	1	<	10	%

Classification (Regulation (EC) No. 1272/2008)

Skin Irrit. 2	H315
Eye Irrit. 2	H319

1,2-Benzisothiazol-3(2h)-one

CAS No.	2634-33-5				
EINECS no.	220-120-9				
Concentration			<	0,05	%

Classification (Regulation (EC) No. 1272/2008)

Aquatic Acute 1	H400
Skin Sens. 1	H317
Acute Tox. 4	H302
Skin Irrit. 2	H315
Eye Dam. 1	H318

Concentration limits (Regulation (EC) No. 1272/2008)

Skin Sens. 1	H317	>= 0,05
--------------	------	---------

A mixture of: 5-Chloro-2-methyl-2h-isothiazol-3-one [EC-no. 247-500-7] and 2-Methyl-2H-isothiazol-3-one [EC-no. 220-239-6] (3:1)

CAS No.	55965-84-9				
Concentration			<	0,0015	%

Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 3	H331
Aquatic Chronic 1	H410
Aquatic Acute 1	H400
Skin Sens. 1	H317
Skin Corr. 1B	H314
Acute Tox. 3	H311
Acute Tox. 3	H301

Concentration limits (Regulation (EC) No. 1272/2008)

Skin Corr. 1B	H314	>= 0,6
Eye Irrit. 2	H319	<= 0,06 < 0,6
Skin Irrit. 2	H315	<= 0,06 < 0,6
Skin Sens. 1	H317	>= 0,0015

SECTION 4: First aid measures**4.1. Description of first aid measures****After skin contact**

Wash with plenty of water and soap. Do NOT use solvents or thinners.

After eye contact

Separate eyelids, wash the eyes thoroughly with water (15 min.). In case of irritation consult an oculist.

After ingestion

Rinse mouth thoroughly with water. If larger amounts are swallowed or in the event of symptoms take medical treatment.



Trade name: Marabu-Porcelain 555, 15 ml Marabu-Porcelain 555, 15 ml

Version: 4 / GB

Date revised: 17.12.2015

Substance number: 110539555

Replaces Version: 3 / GB

Print date: 17.12.15

4.2. Most important symptoms and effects, both acute and delayed

Until now no symptoms known so far.

4.3. Indication of any immediate medical attention and special treatment needed

Hints for the physician / treatment

Treat symptomatically

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide, Foam, Sand, Water

5.2. Special hazards arising from the substance or mixture

In the event of fire the following can be released: Carbon dioxide (CO₂); Carbon monoxide (CO); dense black smoke

5.3. Advice for firefighters

Other information

Collect contaminated fire-fighting water separately, must not be discharged into the drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No particular measures required.

6.2. Environmental precautions

No particular measures required.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent - avoid use of solvents.

6.4. Reference to other sections

Information regarding Safe handling, see Section 7. Information regarding personal protective measures, see Section 8. Information regarding waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid skin and eye contact. Smoking, eating and drinking shall be prohibited in application area.

Advice on protection against fire and explosion

No special measures required.

Classification of fires / temperature class / Ignition group / Dust explosion class

Temperature class T4

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store in frostfree conditions.

7.3. Specific end use(s)

Paint

SECTION 8: Exposure controls/personal protection



Trade name: Marabu-Porcelain 555, 15 ml Marabu-Porcelain 555, 15 ml

Version: 4 / GB

Date revised: 17.12.2015

Substance number: 110539555

Replaces Version: 3 / GB

Print date: 17.12.15

8.1. Control parameters

Other information

There are not known any further control parameters.

Derived No/Minimal Effect Levels (DNEL/DMEL)

3-Butoxypropan-2-ol

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	oral	
Mode of action	Systemic effects	
Concentration	8,75	mg/kg

Predicted No Effect Concentration (PNEC)

3-Butoxypropan-2-ol

Type of value	PNEC	
Type	Soil	
Concentration	0,16	mg/kg
Type of value	PNEC	
Type	Water	
Concentration	0,525	mg/l
Type of value	PNEC	
Type	Freshwater sediment	
Concentration	2,36	mg/kg
Type of value	PNEC	
Type	Aquatic	
Concentration	0,0525	mg/l
Type of value	PNEC	
Type	Marine sediment	
Concentration	0,236	mg/kg
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	10	mg/l

8.2. Exposure controls

Exposure controls

Provide adequate ventilation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form	liquid
Colour	coloured
Odour	solvent-like

Odour threshold

Remarks No data available

pH value

Value 8 to 9



Trade name: Marabu-Porcelain 555, 15 ml Marabu-Porcelain 555, 15 ml

Version: 4 / GB

Date revised: 17.12.2015

Substance number: 110539555

Replaces Version: 3 / GB

Print date: 17.12.15

Temperature 20 °C
Method WTW PH 340

Melting point

Remarks not determined

Freezing point

Remarks not determined

Initial boiling point and boiling range

Value appr. 100 °C
Pressure 1.013 hPa
Source Literature value

Flash point

Remarks Not applicable

Evaporation rate (ether = 1) :

Remarks not determined

Flammability (solid, gas)

Not applicable

Upper/lower flammability or explosive limits

Lower explosion limit appr. 0,6 %(V)
Upper explosion limit appr. 20,4 %(V)
Source Literature value

Vapour pressure

Value appr. 23 hPa
Temperature 20 °C
Method Value taken from the literature

Vapour density

Remarks not determined

Density

Value 1,070 g/cm³
Temperature 20 °C
Method DIN EN ISO 2811

Solubility in water

Remarks miscible

Ignition temperature

Value appr. 189 °C
Source Literature value

Viscosity

Value 2500 to 5000 mPa.s
Temperature 20 °C
Method Brookfield

9.2. Other information

Other information

None known

SECTION 10: Stability and reactivity

10.1. Reactivity

None

10.2. Chemical stability

No hazardous reactions known.



Trade name: Marabu-Porcelain 555, 15 ml Marabu-Porcelain 555, 15 ml

Version: 4 / GB

Date revised: 17.12.2015

Substance number: 110539555

Replaces Version: 3 / GB

Print date: 17.12.15

10.3. Possibility of hazardous reactions

No hazardous reactions known.

10.4. Conditions to avoid

No hazardous reactions known.

10.5. Incompatible materials

None

10.6. Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Aspiration hazard

No special hazards have to be mentioned.

Experience in practice

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Other information

There are no data available on the mixture itself.

The mixture has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and not classified.

SECTION 12: Ecological information

12.1. Toxicity

General information

There are no data available on the mixture itself. Do not allow to enter drains or water courses. The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as dangerous for the environment.

12.2. Persistence and degradability

General information

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

General information

There are no data available on the mixture itself.

12.4. Mobility in soil

General information

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment



Trade name: Marabu-Porcelain 555, 15 ml Marabu-Porcelain 555, 15 ml

Version: 4 / GB

Date revised: 17.12.2015

Substance number: 110539555

Replaces Version: 3 / GB

Print date: 17.12.15

General information

There are no data available on the mixture itself.

12.6. Other adverse effects

General information

There are no data available on the mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations for the product

The product can be placed with other household refuse. Small residues in containers can be washed-out with water and put into the drainage system.

Disposal recommendations for packaging

Packaging that cannot be cleaned should be disposed off as product waste.
Completely emptied packagings can be given for recycling.

SECTION 14: Transport information

Land transport ADR/RID

Non-dangerous goods

14.1. UN number

UN -

14.2. UN proper shipping name

-

14.3. Transport hazard class(es)

Class -

Label -

14.4. Packing group

Packing group -

Transport category 0

14.5. Environmental hazards

-

Marine transport IMDG/GGVSee

The product does not constitute a hazardous substance in sea transport.

14.1. UN number

UN -

14.2. UN proper shipping name

-

14.3. Transport hazard class(es)

Class -

Subsidiary risk -

14.4. Packing group

Packing group -

14.5. Environmental hazards

no

Air transport ICAO/IATA

The product does not constitute a hazardous substance in air transport.

14.1. UN number

UN -

14.2. UN proper shipping name

-

14.3. Transport hazard class(es)

Class -



Trade name: Marabu-Porcelain 555, 15 ml Marabu-Porcelain 555, 15 ml

Version: 4 / GB

Date revised: 17.12.2015

Substance number: 110539555

Replaces Version: 3 / GB

Print date: 17.12.15

Subsidiary risk -
14.4. Packing group
 Packing group -
14.5. Environmental hazards
 -

Information for all modes of transport

14.6. Special precautions for user

Transport within the user's premises:
 Always transport in closed containers that are upright and secure.
 Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Other information

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

no

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC

VOC (EU)	5,59	%	59,8	g/l
----------	------	---	------	-----

Other information

The product does not contain substances of very high concern (SVHC).

Other information

All components are contained in the TSCA inventory or exempted.
 All components are contained in the AICS inventory.
 All components are contained in the PICCS inventory.
 All components are contained in the DSL or NDSL inventory.
 All components are contained in the IECSC inventory.
 All components are contained in the ECL inventory.

15.2. Chemical safety assessment

For this preparation a chemical safety assessment has not been carried out.

SECTION 16: Other information

Hazard statements listed in Chapter 3

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

CLP categories listed in Chapter 3

Acute Tox. 3	Acute toxicity, Category 3
Acute Tox. 4	Acute toxicity, Category 4
Aquatic Acute 1	Hazardous to the aquatic environment, acute, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic, Category 1
Eye Dam. 1	Serious eye damage, Category 1
Eye Irrit. 2	Eye irritation, Category 2

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Marabu-Porcelain 555, 15 ml Marabu-Porcelain 555, 15 ml

Version: 4 / GB

Date revised: 17.12.2015

Substance number: 110539555

Replaces Version: 3 / GB

Print date: 17.12.15

Skin Corr. 1B

Skin corrosion, Category 1B

Skin Irrit. 2

Skin irritation, Category 2

Skin Sens. 1

Skin sensitization, Category 1

Supplemental information

Relevant changes compared with the previous version of the safety data sheet are marked with: ***

This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.

The information in this Safety Data Sheet is based on the present state of knowledge and current legislation.

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions.

As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.