



Trade name: Marabu-GlasArt 498, 15 ml Marabu-GlasArt 498, 15 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130239498

Replaces Version: 6 / GB

Print date: 17.12.15

## **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

### **1.1. Product identifier**

Marabu-GlasArt 498, 15 ml Marabu-GlasArt 498, 15 ml

### **1.2. Relevant identified uses of the substance or mixture and uses advised against**

#### **Use of the substance/preparation**

Paint

### **1.3. Details of the supplier of the safety data sheet**

#### **Address**

Marabu GmbH & Co. KG

Asperger Strasse 4

71732 Tamm

Germany

Telephone no. +49-7141/691-0

Fax no. +49-7141/691-147

Information provided by / telephone Department product safety

E-mail address of person responsible PRSI@marabu.de

for this SDS

### **1.4. Emergency telephone number**

(+49) (0)621-60-43333

## **SECTION 2: Hazards identification \*\*\***

### **2.1. Classification of the substance or mixture**

#### **Classification (Regulation (EC) No. 1272/2008)**

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3	H226
STOT SE 3	H336

### **2.2. Label elements**

#### **Labelling according to regulation (EC) No 1272/2008**

#### **Hazard pictograms**



#### **Signal word**

Warning

#### **Hazard statements \*\*\***

H226	Flammable liquid and vapour.
H336	May cause drowsiness or dizziness.

#### **Precautionary statements**

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition



Trade name: Marabu-GlasArt 498, 15 ml Marabu-GlasArt 498, 15 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130239498

Replaces Version: 6 / GB

Print date: 17.12.15

P271 sources. No smoking.  
 P405 Use only outdoors or in a well-ventilated area.  
 P501.9 Store locked up.  
 Dispose of contents/container as problematic waste.

**Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)**

contains \*\*\* 1-Methoxy-2-propanol;Naphtha (petroleum), hydrotreated heavy

**2.3. Other hazards**

No special hazards have to be mentioned.

**SECTION 3: Composition/information on ingredients \*\*\*****3.2. Mixtures****Chemical characterization**

Paint based on alkyd resins and on solvents

**Hazardous ingredients \*\*\*****1-Methoxy-2-propanol**

CAS No. 107-98-2  
 EINECS no. 203-539-1  
 Registration no. 01-2119457435-35  
 Concentration >= 25 < 50 %

Classification (Regulation (EC) No. 1272/2008)

STOT SE 3 H336  
 Flam. Liq. 3 H226

**Naphtha (petroleum), hydrotreated heavy**

CAS No. 64742-48-9  
 EINECS no. 919-857-5  
 Registration no. 01-2119463258-33  
 Concentration >= 10 < 20 %

Classification (Regulation (EC) No. 1272/2008)

Asp. Tox. 1 H304  
 Flam. Liq. 3 H226  
 STOT SE 3 H336  
 EUH066

**2-Butoxyethyl acetate**

CAS No. 112-07-2  
 EINECS no. 203-933-3  
 Registration no. 01-2119475112-47  
 Concentration >= 1 < 10 %

Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 4 H332  
 Acute Tox. 4 H312  
 Acute Tox. 4 H302

**C.I.Solvent Blue 70**

CAS No. 94277-77-7  
 EINECS no. 304-661-9  
 Concentration >= 1 < 10 %

Classification (Regulation (EC) No. 1272/2008)



Trade name: Marabu-GlasArt 498, 15 ml Marabu-GlasArt 498, 15 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130239498

Replaces Version: 6 / GB

Print date: 17.12.15

Aquatic Chronic 3 H412

**Hexanoic acid, 2-ethyl-, zinc salt, basic**

CAS No. 85203-81-2

EINECS no. 286-272-3

Registration no. 01-2119979093-30

Concentration &gt;= 0,1 &lt; 1 %

Classification (Regulation (EC) No. 1272/2008)

Eye Irrit. 2 H319

Repr. 2 H361d

Aquatic Chronic 3 H412

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

**After inhalation**

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

**After skin contact**

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

**After eye contact**

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

**After ingestion**

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

**4.2. Most important symptoms and effects, both acute and delayed**

Until now no symptoms known so far.

**4.3. Indication of any immediate medical attention and special treatment needed****Hints for the physician / treatment**

Treat symptomatically

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Recommended: alcohol resistant foam, CO<sub>2</sub>, powders, water spray/mist, Not be used for safety reasons: water jet

**5.2. Special hazards arising from the substance or mixture**

In the event of fire the following can be released: Carbon monoxide (CO); Carbon dioxide (CO<sub>2</sub>); dense black smoke; Nitrogen oxides (NO<sub>x</sub>)

**5.3. Advice for firefighters****Special protective equipment for fire-fighting**

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or



Trade name: Marabu-GlasArt 498, 15 ml Marabu-GlasArt 498, 15 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130239498

Replaces Version: 6 / GB

Print date: 17.12.15

water courses.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in Sections 7 and 8.

### **6.2. Environmental precautions**

Do not allow to enter drains or waterways. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

### **6.3. Methods and material for containment and cleaning up**

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

### **6.4. Reference to other sections**

Information regarding Safe handling, see Section 7. Information regarding personal protective measures, see Section 8. Information regarding waste disposal, see Section 13.

## **SECTION 7: Handling and storage**

### **7.1. Precautions for safe handling**

#### **Advice on safe handling**

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Avoid skin and eye contact. Avoid the inhalation of particulates and spray mist arising from the application of this mixture. Smoking, eating and drinking shall be prohibited in application area. For personal protection see Section 8. Never use pressure to empty: container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or water courses.

#### **Advice on protection against fire and explosion**

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

#### **Classification of fires / temperature class / Ignition group / Dust explosion class**

Classification of fires	B (Combustible liquid substances)
Temperature class	T4

### **7.2. Conditions for safe storage, including any incompatibilities**

#### **Requirements for storage rooms and vessels**

Electrical installations/working materials must comply with the local applied technological safety standards. Storage rooms in which filling operations take place must have a conducting floor. Store in accordance with national regulation

#### **Hints on storage assembly**

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

#### **Further information on storage conditions**

Observe label precautions. Store between 15 and 30 °C in a dry, well ventilated place away from sources of heat and direct sunlight. Keep container tightly closed. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.



Trade name: Marabu-GlasArt 498, 15 ml Marabu-GlasArt 498, 15 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130239498

Replaces Version: 6 / GB

Print date: 17.12.15

**7.3. Specific end use(s)**

Paint

**SECTION 8: Exposure controls/personal protection \*\*\***

**8.1. Control parameters**

**Exposure limit values \*\*\***

**1-Methoxy-2-propanol**

List	EH40		
Type	WEL		
Value	375	mg/m <sup>3</sup>	100 ppm(V)
Short term exposure limit	560	mg/m <sup>3</sup>	150 ppm(V)
Skin resorption / sensibilisation: Sk; Status: 2011			

**2-Butoxyethyl acetate**

List	EH40		
Type	WEL		
Value	133		20 ppm(V)
Short term exposure limit	332		50 ppm(V)
Skin resorption / sensibilisation: Sk; Status: 2011			

**Normal and branched chain alkanes, >=C7**

List	EH40		
Value	1200	mg/m <sup>3</sup>	

**Cycloalkanes, >=C7**

List	EH40		
Value	800	mg/m <sup>3</sup>	
List	HTP		
Value			900 ppm(V)
Short term exposure limit		1200	
Maximum limit value: ppm			

**Derived No/Minimal Effect Levels (DNEL/DMEL) \*\*\***

**2-Butoxyethyl acetate**

Reference substance	2-Butoxyethyl acetate		
Type of value	Derived No Effect Level (DNEL)		
Reference group	Worker		
Route of exposure	dermal		
Mode of action	Acute effects		
Concentration	102		mg/kg
Source	Literature value		

Type of value	2-Butoxyethyl acetate		
	Derived No Effect Level (DNEL)		
Reference group	Worker		
Route of exposure	inhalative		
Mode of action	Acute effects		
Concentration	775		mg/kg
Source	Literature value		

Type of value	2-Butoxyethyl acetate		
	Derived No Effect Level (DNEL)		
Reference group	Consumer		
Route of exposure	dermal		
Mode of action	Acute effects		
Concentration	27		mg/kg
Source	Literature value		

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Marabu-GlasArt 498, 15 ml Marabu-GlasArt 498, 15 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130239498

Replaces Version: 6 / GB

Print date: 17.12.15

Type of value 2-Butoxyethyl acetate  
 Derived No Effect Level (DNEL)  
 Reference group Consumer  
 Route of exposure inhalative  
 Concentration 499 mg/kg  
 Source Literature value

Type of value 2-Butoxyethyl acetate  
 Derived No Effect Level (DNEL)  
 Reference group Consumer  
 Route of exposure oral  
 Mode of action Acute effects  
 Concentration 18 mg/kg  
 Source Literature value

Type of value 2-Butoxyethyl acetate  
 Derived No Effect Level (DNEL)  
 Reference group Consumer  
 Route of exposure inhalative  
 Mode of action Local effects  
 Concentration 166 mg/kg  
 Source Literature value

Type of value 2-Butoxyethyl acetate  
 Derived No Effect Level (DNEL)  
 Reference group Consumer  
 Route of exposure dermal  
 Mode of action Chronic effects  
 Concentration 36 mg/kg  
 Source Literature value

Type of value 2-Butoxyethyl acetate  
 Derived No Effect Level (DNEL)  
 Reference group Consumer  
 Route of exposure inhalative  
 Mode of action Chronic effects  
 Concentration 67 mg/kg  
 Source Literature value

Type of value 2-Butoxyethyl acetate  
 Derived No Effect Level (DNEL)  
 Reference group Consumer  
 Route of exposure oral  
 Mode of action Chronic effects  
 Concentration 4,3 mg/kg  
 Source Literature value

Type of value 2-Butoxyethyl acetate  
 Derived No Effect Level (DNEL)  
 Reference group Worker  
 Route of exposure dermal  
 Mode of action Chronic effects  
 Concentration 102 mg/kg  
 Source Literature value

Type of value 2-Butoxyethyl acetate  
 Derived No Effect Level (DNEL)

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Marabu-GlasArt 498, 15 ml Marabu-GlasArt 498, 15 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130239498

Replaces Version: 6 / GB

Print date: 17.12.15

Reference group	Worker	
Route of exposure	inhalative	
Mode of action	Chronic effects	
Concentration	133	mg/kg
Source	Literature value	

**1-Methoxy-2-propanol**

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Acute	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	553,5	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	50,6	mg/person/ d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	369	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	General Population	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	18,1	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	General Population	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	43,9	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	General Population	
Duration of exposure	Long term	
Route of exposure	oral	
Mode of action	Systemic effects	
Concentration	3,3	mg/kg/d

**Naphtha (petroleum), hydrotreated heavy**

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	300	mg/kg

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Marabu-GlasArt 498, 15 ml Marabu-GlasArt 498, 15 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130239498

Replaces Version: 6 / GB

Print date: 17.12.15

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	oral	
Mode of action	Systemic effects	
Concentration	300	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	300	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	900	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	1500	mg/m <sup>3</sup>

**Predicted No Effect Concentration (PNEC)**

**2-Butoxyethyl acetate**

Reference substance	2-Butoxyethyl acetate	
Type of value	PNEC	
Type	Water	
Concentration	0,304	mg/l
Source	Literature value	

Type of value	2-Butoxyethyl acetate	
Type	PNEC	
Type	Aquatic	
Concentration	0,0304	g/l
Source	Literature value	

Type of value	2-Butoxyethyl acetate	
Type	PNEC	
Type	Sediment	
Concentration	2,03	mg/kg
Source	Literature value	

Type of value	2-Butoxyethyl acetate	
Type	PNEC	
Type	Marine sediment	
Concentration	0,203	mg/kg
Source	Literature value	

Type of value	2-Butoxyethyl acetate	
Type	PNEC	





Trade name: Marabu-GlasArt 498, 15 ml Marabu-GlasArt 498, 15 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130239498

Replaces Version: 6 / GB

Print date: 17.12.15

Type	Soil	
Concentration	0,68	mg/kg
Source	Literature value	

**1-Methoxy-2-propanol**

Type of value	PNEC	
Type	Freshwater	
Concentration	10	mg/l
Type of value	PNEC	
Type	Water	
Concentration	41,6	mg/kg
Type of value	PNEC	
Type	Sediment	
Concentration	41,6	mg/kg
Type of value	PNEC	
Type	Marine sediment	
Concentration	4,17	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	2,47	mg/kg
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	100	mg/l

**8.2. Exposure controls**

**Exposure controls**

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

**Respiratory protection**

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. Full mask, filter A

**Hand protection**

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.  
 For prolonged or repeated handling nitrile rubber gloves with textile undergloves are required. The breakthrough time must be greater than the end use time of the product.  
 The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.  
 Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly.  
 The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.  
 Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

**Eye protection**

Use safety eyewear designed to protect against splash of liquids.

**Body protection**

Cotton or cotton/synthetic overalls or coveralls are normally suitable.



Trade name: Marabu-GlasArt 498, 15 ml Marabu-GlasArt 498, 15 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130239498

Replaces Version: 6 / GB

Print date: 17.12.15

## **SECTION 9: Physical and chemical properties**

### **9.1. Information on basic physical and chemical properties**

<b>Form</b>	Liquid		
<b>Colour</b>	coloured		
<b>Odour</b>	solvent-like		
<b>Odour threshold</b>			
Remarks	No data available		
<b>pH value</b>			
Remarks	Not applicable		
<b>Melting point</b>			
Remarks	not determined		
<b>Freezing point</b>			
Remarks	not determined		
<b>Initial boiling point and boiling range</b>			
Value	appr. 120		°C
Pressure	1.013	hPa	
Source	Literature value		
<b>Flash point</b>			
Value	48		°C
Method	ASTM D 6450 (CCCFP)		
<b>Evaporation rate (ether = 1) :</b>			
Remarks	not determined		
<b>Flammability (solid, gas)</b>			
Not applicable			
<b>Upper/lower flammability or explosive limits</b>			
Lower explosion limit	appr. 0,7		%(V)
Upper explosion limit	appr. 13,7		%(V)
Source	Literature value		
<b>Vapour pressure</b>			
Value	appr. 8		hPa
Temperature	20	°C	
Method	calculated		
<b>Vapour density</b>			
Remarks	not determined		
<b>Density</b>			
Value	0,93		g/cm <sup>3</sup>
Temperature	20	°C	
Method	DIN EN ISO 2811		
<b>Solubility in water</b>			
Remarks	partially miscible		
<b>Partition coefficient: n-octanol/water</b>			
Remarks	Not applicable		
<b>Ignition temperature</b>			
Value	appr. 200		°C
Source	Literature value		
<b>Efflux time</b>			
Value	< 40	to	75 s



Trade name: Marabu-GlasArt 498, 15 ml Marabu-GlasArt 498, 15 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130239498

Replaces Version: 6 / GB

Print date: 17.12.15

Temperature 20 °C

Method DIN 53211 4 mm

**Explosive properties**

evaluation no

**Oxidising properties**

evaluation None known

**9.2. Other information****Other information**

The physical specifications are approximate values and refer to the used safety relevant component(s).

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No hazardous reactions when stored and handled according to prescribed instructions.

**10.2. Chemical stability**

Stable under recommended storage and handling conditions (see section 7).

**10.3. Possibility of hazardous reactions**

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

**10.4. Conditions to avoid**

When exposed to high temperatures may produce hazardous decomposition products.

**10.5. Incompatible materials**

No hazardous reactions when stored and handled according to prescribed instructions.

**10.6. Hazardous decomposition products**

See chapter 5.2 (Firefighting measures - Special hazards arising from the substance or mixture).

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute oral toxicity**

ATE &gt; 2.000 mg/kg

Method calculated value (Regulation (EC) No. 1272/2008)

**Acute oral toxicity (Components)****1-Methoxy-2-propanol**

Species rat

LD50 5200 mg/kg

**Acute dermal toxicity**

ATE &gt; 2.000 mg/kg

Method calculated value (Regulation (EC) No. 1272/2008)

**Acute dermal toxicity (Components)****1-Methoxy-2-propanol**

Species rabbit

LD50 14000 mg/kg

**Acute inhalational toxicity**

ATE &gt; 20 mg/l

Administration/Form Vapors

Method calculated value (Regulation (EC) No. 1272/2008)

ATE &gt; 5 mg/l



Trade name: Marabu-GlasArt 498, 15 ml Marabu-GlasArt 498, 15 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130239498

Replaces Version: 6 / GB

Print date: 17.12.15

Administration/Form                      Dust/Mist  
Method    calculated value (Regulation (EC) No. 1272/2008)

**Aspiration hazard**

No special hazards have to be mentioned.

**Experience in practice**

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

**Other information**

There are no data available on the mixture itself.

The mixture has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly.

**SECTION 12: Ecological information****12.1. Toxicity****General information**

There are no data available on the mixture itself. Do not allow to enter drains or water courses. The mixture has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment, but contains substance(s) dangerous for the environment. See section 3 for details.

**Fish toxicity (Components)****1-Methoxy-2-propanol**

Species	golden orfe ( <i>Leuciscus idus</i> )	
LC0	> 4600	mg/l
Duration of exposure	96 h	

**Daphnia toxicity (Components)****1-Methoxy-2-propanol**

Species	<i>Daphnia magna</i>	
EC50	23300	mg/l
Duration of exposure	48 h	

**Algae toxicity (Components)****1-Methoxy-2-propanol**

Species	<i>Desmodesmus</i>	
EC50	> 1000	mg/l
Duration of exposure	168 h	

**Bacteria toxicity (Components)****1-Methoxy-2-propanol**

Species	activated sludge	
EC50	> 1000	mg/l

**12.2. Persistence and degradability****General information**

No data available



Trade name: Marabu-GlasArt 498, 15 ml Marabu-GlasArt 498, 15 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130239498

Replaces Version: 6 / GB

Print date: 17.12.15

### Biodegradability (Components)

#### 1-Methoxy-2-propanol

Value	90	%
Duration of test evaluation	28	d
Method	Readily biodegradable (according to OECD criteria) OECD 301 F	

### 12.3. Bioaccumulative potential

#### General information

There are no data available on the mixture itself.

#### Partition coefficient: n-octanol/water

Remarks Not applicable

### 12.4. Mobility in soil

#### General information

There are no data available on the mixture itself.

### 12.5. Results of PBT and vPvB assessment

#### General information

There are no data available on the mixture itself.

### 12.6. Other adverse effects

#### General information

There are no data available on the mixture itself.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Disposal recommendations for the product

Do not allow to enter drains or water courses.

Wastes and emptied containers should be classified in accordance with relevant national regulation.

The European Waste Catalogue classification of this product, when disposed of as waste is

EWC waste code 08 01 11\* waste paint and varnish containing organic solvents or other dangerous substances

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

For further information contact your local waste authority.

#### Disposal recommendations for packaging

Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Not emptied containers are hazardous waste (waste code number 150110).

## SECTION 14: Transport information

### Land transport ADR/RID

#### 14.1. UN number

UN 1263

#### 14.2. UN proper shipping name

PAINT

#### 14.3. Transport hazard class(es)

Class 3

Label 3

#### 14.4. Packing group



Trade name: Marabu-GlasArt 498, 15 ml Marabu-GlasArt 498, 15 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130239498

Replaces Version: 6 / GB

Print date: 17.12.15

Packing group III  
 Special provision 640E  
 Limited Quantity 5 l  
 Transport category 4

**14.5. Environmental hazards**

-  
 Tunnel restriction code D/E

**Marine transport IMDG/GGVSee**

**14.1. UN number**

UN 1263

**14.2. UN proper shipping name**

PAINT

**14.3. Transport hazard class(es)**

Class 3

**14.4. Packing group**

Packing group III

**14.5. Environmental hazards**

no

**Air transport ICAO/IATA**

**14.1. UN number**

UN 1263

**14.2. UN proper shipping name**

PAINT

**14.3. Transport hazard class(es)**

Class 3

**14.4. Packing group**

Packing group III

**14.5. Environmental hazards**

-

**Information for all modes of transport**

**14.6. Special precautions for user**

Transport within the user's premises:  
 Always transport in closed containers that are upright and secure.  
 Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Other information**

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

no

**SECTION 15: Regulatory information \*\*\***

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Major-accident categories acc. 96/82/EC**

Category	6	Flammable	5.000.000	kg	50.000.000	kg
----------	---	-----------	-----------	----	------------	----

**VOC \*\*\***

VOC (EU)	34,24	%	318,4	g/l
----------	-------	---	-------	-----

**Other information**

The product does not contain substances of very high concern (SVHC).

**Other information**

All components are contained in the TSCA inventory or exempted.  
 All components are contained in the AICS inventory.  
 All components are contained in the PICCS inventory.



Trade name: Marabu-GlasArt 498, 15 ml Marabu-GlasArt 498, 15 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130239498

Replaces Version: 6 / GB

Print date: 17.12.15

All components are contained in the DSL inventory.  
All components are contained in the ENCS inventory.

## 15.2. Chemical safety assessment

For this preparation a chemical safety assessment has not been carried out.

## **SECTION 16: Other information**

### **Hazard statements listed in Chapter 3**

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H412	Harmful to aquatic life with long lasting effects.

### **CLP categories listed in Chapter 3**

Acute Tox. 4	Acute toxicity, Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Eye irritation, Category 2
Flam. Liq. 3	Flammable liquid, Category 3
Repr. 2	Reproductive toxicity, Category 2
STOT SE 3	Specific target organ toxicity - single exposure, Category 3

### **Supplemental information**

Relevant changes compared with the previous version of the safety data sheet are marked with: \*\*\*  
This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.  
The information in this Safety Data Sheet is based on the present state of knowledge and current legislation.

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions.

As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.