



Trade name: Marabu Alcohol Ink 091, 20ml MNA

Version: 2 / GB

Date revised: 17.07.2019

Substance number: 12169007091

Replaces Version: 1 / GB

Print date: 07.08.19

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Marabu Alcohol Ink 091, 20ml MNA

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/preparation

Paint

Identified Uses

SU21

Consumer uses: Private households (= general public = consumers)

PC9a

Coatings and paints, thinners, paint removers

1.3. Details of the supplier of the safety data sheet

Address

Marabu GmbH & Co. KG

Asperger Strasse 4

71732 Tamm

Germany

Telephone no. +49-7141/691-0

Fax no. +49-7141/691-147

Information provided Department product safety

by / telephone

E-mail address of PRSI@marabu.de

person responsible

for this SDS

1.4. Emergency telephone number

(+49) (0)621-60-43333

SECTION 2: Hazards identification ***

2.1. Classification of the substance or mixture

Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 2 H225

Eye Irrit. 2 H319

STOT SE 3 H336

2.2. Label elements

Labelling according to regulation (EC) No 1272/2008

Hazard pictograms



Signal word

Danger

Hazard statements

H225

Highly flammable liquid and vapour.

H319

Causes serious eye irritation.



Trade name: Marabu Alcohol Ink 091, 20ml MNA

Version: 2 / GB

Date revised: 17.07.2019

Substance number: 12169007091

Replaces Version: 1 / GB

Print date: 07.08.19

H336 May cause drowsiness or dizziness.

Precautionary statements ***

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P264.1 Wash hands thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P405 Store locked up.
- P501.9 Dispose of contents/container as problematic waste.

Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

contains Acetone;Propan-2-ol

Supplemental information

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No special hazards have to be mentioned.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients

Propan-2-ol

CAS No. 67-63-0
 EINECS no. 200-661-7
 Registration no. 01-2119457558-25
 Concentration >= 50 < 100 %

Classification (Regulation (EC) No. 1272/2008)
 Flam. Liq. 2 H225
 Eye Irrit. 2 H319
 STOT SE 3 H336

Acetone

CAS No. 67-64-1
 EINECS no. 200-662-2
 Registration no. 01-2119471330-49
 Concentration >= 20 < 25 %

Classification (Regulation (EC) No. 1272/2008)
 Flam. Liq. 2 H225
 Eye Irrit. 2 H319
 STOT SE 3 H336

2-(Propyloxy)ethanol

CAS No. 2807-30-9
 EINECS no. 220-548-6
 Concentration >= 1 < 10 %

Classification (Regulation (EC) No. 1272/2008)
 Acute Tox. 4 H312
 Eye Irrit. 2 H319



Trade name: Marabu Alcohol Ink 091, 20ml MNA

Version: 2 / GB

Date revised: 17.07.2019

Substance number: 12169007091

Replaces Version: 1 / GB

Print date: 07.08.19

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Until now no symptoms known so far.

4.3. Indication of any immediate medical attention and special treatment needed

Hints for the physician / treatment

Treat symptomatically

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Recommended: alcohol resistant foam, CO₂, powders, water spray/mist, Not be used for safety reasons: water jet

5.2. Special hazards arising from the substance or mixture

In the event of fire the following can be released: Carbon monoxide (CO); Carbon dioxide (CO₂); dense black smoke

5.3. Advice for firefighters

Special protective equipment for fire-fighting

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Do not allow to enter drains or waterways. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up



Trade name: Marabu Alcohol Ink 091, 20ml MNA

Version: 2 / GB

Date revised: 17.07.2019

Substance number: 12169007091

Replaces Version: 1 / GB

Print date: 07.08.19

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4. Reference to other sections

Information regarding Safe handling, see Section 7. Information regarding personal protective measures, see Section 8. Information regarding waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Avoid skin and eye contact. Avoid the inhalation of particulates and spray mist arising from the application of this mixture. Smoking, eating and drinking shall be prohibited in application area. For personal protection see Section 8. Never use pressure to empty: container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or water courses.

Advice on protection against fire and explosion

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

Classification of fires / temperature class / Ignition group / Dust explosion class

Classification of fires	B (Combustible liquid substances)
Temperature class	T2

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Electrical installations/working materials must comply with the local applied technological safety standards. Storage rooms in which filling operations take place must have a conducting floor. Store in accordance with national regulation

Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

Further information on storage conditions

Observe label precautions. Store between 15 and 30 °C in a dry, well ventilated place away from sources of heat and direct sunlight. Keep container tightly closed. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

7.3. Specific end use(s)

Paint

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limit values

Acetone

List	EH40		
Type	WEL		
Value	1210	mg/m ³	500 ppm(V)

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Marabu Alcohol Ink 091, 20ml MNA

Version: 2 / GB

Date revised: 17.07.2019

Substance number: 12169007091

Replaces Version: 1 / GB

Print date: 07.08.19

Short term exposure limit	3620	mg/m ³	1500	ppm(V)
Status: 2011				

Propan-2-ol

List	EH40			
Type	WEL			
Value	999	mg/m ³	400	ppm(V)
Short term exposure limit	1250	mg/m ³	500	ppm(V)
Status: 2011				

Derived No/Minimal Effect Levels (DNEL/DMEL)

Acetone

Type of value	Derived No Effect Level (DNEL)			
Reference group	Worker			
Duration of exposure	Long term			
Route of exposure	dermal			
Concentration	186			mg/kg/d

Type of value	Derived No Effect Level (DNEL)			
Reference group	Worker			
Duration of exposure	Short term			
Route of exposure	inhalative			
Concentration	2420			mg/m ³

Type of value	Derived No Effect Level (DNEL)			
Reference group	Worker			
Duration of exposure	Long term			
Route of exposure	inhalative			
Concentration	1210			mg/m ³

Type of value	Derived No Effect Level (DNEL)			
Reference group	Consumer			
Duration of exposure	Long term			
Route of exposure	oral			
Concentration	62			mg/kg/d

Type of value	Derived No Effect Level (DNEL)			
Reference group	Consumer			
Duration of exposure	Long term			
Concentration	62			mg/kg/d

Type of value	Derived No Effect Level (DNEL)			
Reference group	Consumer			
Duration of exposure	Long term			
Route of exposure	inhalative			
Concentration	200			mg/m ³

Propan-2-ol

Type of value	Derived No Effect Level (DNEL)			
Reference group	Worker			
Duration of exposure	Long term			
Route of exposure	inhalative			
Mode of action	Systemic effects			
Concentration	500			mg/m ³

Type of value	Derived No Effect Level (DNEL)			
Reference group	Worker			
Duration of exposure	Long term			

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Marabu Alcohol Ink 091, 20ml MNA

Version: 2 / GB

Date revised: 17.07.2019

Substance number: 12169007091

Replaces Version: 1 / GB

Print date: 07.08.19

Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	888	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	General Population	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	89	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	General Population	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	319	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	General Population	
Duration of exposure	Long term	
Route of exposure	oral	
Mode of action	Systemic effects	
Concentration	26	mg/kg/d

Predicted No Effect Concentration (PNEC)

Acetone

Type of value	PNEC	
Type	Freshwater	
Concentration	10,6	mg/l
Type of value	PNEC	
Type	Saltwater	
Concentration	1,06	mg/l
Type of value	PNEC	
Type	Water (intermittent release)	
Concentration	21	mg/l
Type of value	PNEC	
Type	Freshwater sediment	
Concentration	30,4	mg/kg
Type of value	PNEC	
Type	Marine sediment	
Concentration	3,04	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	29,5	mg/kg
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	100	mg/l

Propan-2-ol

Type of value	PNEC	
---------------	------	--



Trade name: Marabu Alcohol Ink 091, 20ml MNA

Version: 2 / GB

Date revised: 17.07.2019

Substance number: 12169007091

Replaces Version: 1 / GB

Print date: 07.08.19

Type	Freshwater	
Concentration	140,9	mg/l
Type of value	PNEC	
Type	Saltwater	
Concentration	140,9	mg/l
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	2251	mg/l
Type of value	PNEC	
Type	Freshwater sediment	
Concentration	552	mg/kg
Type of value	PNEC	
Type	Marine sediment	
Concentration	552	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	28	mg/kg

8.2. Exposure controls

Exposure controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. Full mask, filter A

Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

For prolonged or repeated handling nitrile rubber gloves with textile undergloves are required.

Material thickness > 0,5 mm

Breakthrough time < 30 min

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

Eye protection

Use safety eyewear designed to protect against splash of liquids.

Body protection

Cotton or cotton/synthetic overalls or coveralls are normally suitable.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties



Trade name: Marabu Alcohol Ink 091, 20ml MNA

Version: 2 / GB

Date revised: 17.07.2019

Substance number: 12169007091

Replaces Version: 1 / GB

Print date: 07.08.19

Form	liquid		
Colour	coloured		
Odour	solvent-like		
Odour threshold			
Remarks	No data available		
pH value			
Remarks	Not applicable		
Melting point			
Remarks	not determined		
Freezing point			
Remarks	not determined		
Initial boiling point and boiling range			
Value	appr. 82		°C
Flash point			
Value	20		°C
Evaporation rate (ether = 1) :			
Remarks	not determined		
Flammability (solid, gas)			
Not applicable			
Upper/lower flammability or explosive limits			
Lower explosion limit	appr. 2		%(V)
Upper explosion limit	appr. 13		%(V)
Source	Literature value		
Vapour pressure			
Value	appr. 45		hPa
Vapour density			
Remarks	not determined		
Density			
Remarks	not determined		
Solubility in water			
Remarks	partially miscible		
Partition coefficient: n-octanol/water			
Remarks	Not applicable		
Ignition temperature			
Value	appr. 425		°C
Source	Literature value		
Viscosity			
Value	150	to	250 mPa.s
Efflux time			
Value	< 12		s
Temperature	20		°C
Method	DIN 53211 4 mm		
Explosive properties			
evaluation	no		
Oxidising properties			
evaluation	None known		

9.2. Other information



Trade name: Marabu Alcohol Ink 091, 20ml MNA

Version: 2 / GB

Date revised: 17.07.2019

Substance number: 12169007091

Replaces Version: 1 / GB

Print date: 07.08.19

Other information

The physical specifications are approximate values and refer to the used safety relevant component(s).

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reactions when stored and handled according to prescribed instructions.

10.2. Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3. Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4. Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

10.5. Incompatible materials

No hazardous reactions when stored and handled according to prescribed instructions.

10.6. Hazardous decomposition products

See chapter 5.2 (Firefighting measures - Special hazards arising from the substance or mixture).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute oral toxicity

Remarks Based on available data, the classification criteria are not met.

Acute oral toxicity (Components)

Acetone

Species	rat		
LD50		5800	mg/kg

Acute dermal toxicity (Components)

Acetone

Species	rabbit		
LD50		20000	mg/kg

Acute inhalational toxicity

Remarks Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Remarks Based on available data, the classification criteria are not met.

Serious eye damage/irritation

evaluation	irritant
Remarks	The classification criteria are met.

Sensitization

Remarks Based on available data, the classification criteria are not met.

Mutagenicity

Remarks Based on available data, the classification criteria are not met.

Reproductive toxicity

Remarks Based on available data, the classification criteria are not met.

Carcinogenicity

Remarks Based on available data, the classification criteria are not met.



Trade name: Marabu Alcohol Ink 091, 20ml MNA

Version: 2 / GB

Date revised: 17.07.2019

Substance number: 12169007091

Replaces Version: 1 / GB

Print date: 07.08.19

Specific Target Organ Toxicity (STOT)

Single exposure

Remarks
evaluation

The classification criteria are met.
May cause drowsiness or dizziness.

Repeated exposure

Remarks

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Experience in practice

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Other information

There are no data available on the mixture itself.
The mixture has been assessed following the additivity method of the GHS/CLP Regulation (EC) No 1272/2008.

SECTION 12: Ecological information

12.1. Toxicity

General information

There are no data available on the mixture itself. Do not allow to enter drains or water courses. The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as dangerous for the environment.

12.2. Persistence and degradability

General information

No data available

12.3. Bioaccumulative potential

General information

There are no data available on the mixture itself.

Partition coefficient: n-octanol/water

Remarks

Not applicable

12.4. Mobility in soil

General information

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

General information

There are no data available on the mixture itself.

12.6. Other adverse effects

General information



Trade name: Marabu Alcohol Ink 091, 20ml MNA

Version: 2 / GB

Date revised: 17.07.2019

Substance number: 12169007091

Replaces Version: 1 / GB

Print date: 07.08.19

There are no data available on the mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations for the product

Do not allow to enter drains or water courses.

Wastes and emptied containers should be classified in accordance with relevant national regulation.

The European Waste Catalogue classification of this product, when disposed of as waste is

EWC waste code 08 03 12* waste ink containing dangerous substances

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

For further information contact your local waste authority.

Disposal recommendations for packaging

Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Not emptied containers are hazardous waste (waste code number 150110).

SECTION 14: Transport information

Land transport ADR/RID

14.1. UN number

UN 1263

14.2. UN proper shipping name

PAINT

14.3. Transport hazard class(es)

Class 3

Label 3

14.4. Packing group

Packing group II

Special provision 640D

Limited Quantity 5 I

Transport category 3

14.5. Environmental hazards

-

Tunnel restriction code D/E

Marine transport IMDG/GGVSee

14.1. UN number

UN 1263

14.2. UN proper shipping name

PAINT

14.3. Transport hazard class(es)

Class 3

14.4. Packing group

Packing group II

14.5. Environmental hazards

no

Air transport ICAO/IATA

14.1. UN number

UN 1263

14.2. UN proper shipping name

PAINT

14.3. Transport hazard class(es)

Class 3



Trade name: Marabu Alcohol Ink 091, 20ml MNA

Version: 2 / GB

Date revised: 17.07.2019

Substance number: 12169007091

Replaces Version: 1 / GB

Print date: 07.08.19

14.4. Packing group

Packing group II

14.5. Environmental hazards

-

Information for all modes of transport

14.6. Special precautions for user

Transport within the user's premises:

Always transport in closed containers that are upright and secure.

Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Other information

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

no

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Major-accident categories acc. 96/82/EC

Category	7B	Highly flammable liquids	5.000.000	kg	50.000.000	kg
----------	----	--------------------------	-----------	----	------------	----

Other information

The product does not contain substances of very high concern (SVHC).

15.2. Chemical safety assessment

For this preparation a chemical safety assessment has not been carried out.

SECTION 16: Other information

Hazard statements listed in Chapter 3

H225	Highly flammable liquid and vapour.
H312	Harmful in contact with skin.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

CLP categories listed in Chapter 3

Acute Tox. 4	Acute toxicity, Category 4
Eye Irrit. 2	Eye irritation, Category 2
Flam. Liq. 2	Flammable liquid, Category 2
STOT SE 3	Specific target organ toxicity - single exposure, Category 3

Supplemental information

Relevant changes compared with the previous version of the safety data sheet are marked with: ***
 This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.
 The information in this Safety Data Sheet is based on the present state of knowledge and current legislation.

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.
 The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions.

As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.