Trade name: Marabu Alcohol Ink 158, 20ml MNA

Version: 2 / GB Date revised: 17.07.2019

Substance number: 12169007158 Replaces Version: 1 / GB Print date: 07.08.19

<u>SECTION 1: Identification of the substance/mixture and of the company/undertaking</u>

1.1. Product identifier

Marabu Alcohol Ink 158, 20ml MNA

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/preparation

Paint

Identified Uses

SU21 Consumer uses: Private households (= general public = consumers)

PC9a Coatings and paints, thinners, paint removers

1.3. Details of the supplier of the safety data sheet

Address

Marabu GmbH & Co. KG Asperger Strasse 4 71732 Tamm Germany

Telephone no. +49-7141/691-0 Fax no. +49-7141/691-147

Information provided Department product safety

by / telephone

E-mail address of

PRSI@marabu.de

person responsible

for this SDS

1.4. Emergency telephone number

(+49) (0)621-60-43333

SECTION 2: Hazards identification ***

2.1. Classification of the substance or mixture

Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 2 H225 Eye Irrit. 2 H319 STOT SE 3 H336

2.2. Label elements

Labelling according to regulation (EC) No 1272/2008

Hazard pictograms





Signal word

Danger

Hazard statements

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

Trade name: Marabu Alcohol Ink 158, 20ml MNA

Version: 2 / GB Date revised: 17.07.2019

Substance number: 12169007158 Replaces Version: 1 / GB Print date: 07.08.19

H336 May cause drowsiness or dizziness.

Precautionary statements ***

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P264.1 Wash hands thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501.9 Dispose of contents/container as problematic waste.

Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

contains Acetone; Propan-2-ol

Supplemental information

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No special hazards have to be mentioned.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients

Propan-2-ol

CAS No. 67-63-0 EINECS no. 200-661-7

Registration no. 01-2119457558-25

Concentration >= 50 < 100 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 2 H225 Eye Irrit. 2 H319 STOT SE 3 H336

Acetone

CAS No. 67-64-1 EINECS no. 200-662-2

Registration no. 01-2119471330-49

Concentration >= 20 < 25 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 2 H225 Eye Irrit. 2 H319 STOT SE 3 H336

2-(Propyloxy)ethanol

CAS No. 2807-30-9

EINECS no. 220-548-6

Concentration >= 1 < 10 %

Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 4 H312 Eye Irrit. 2 H319

Trade name: Marabu Alcohol Ink 158, 20ml MNA

Version: 2 / GB Date revised: 17.07.2019

Substance number: 12169007158 Replaces Version: 1 / GB Print date: 07.08.19

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eve contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Until now no symptoms known so far.

4.3. Indication of any immediate medical attention and special treatment needed Hints for the physician / treatment

Treat symptomatically

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Recommended: alcohol resistant foam, CO2, powders, water spray/mist, Not be used for safety reasons: water iet

5.2. Special hazards arising from the substance or mixture

In the event of fire the following can be released: Carbon monoxide (CO); Carbon dioxide (CO2); dense black smoke

5.3. Advice for firefighters

Special protective equipment for fire-fighting

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Do not allow to enter drains or waterways. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Trade name: Marabu Alcohol Ink 158, 20ml MNA

Version: 2 / GB Date revised: 17.07.2019

Substance number: 12169007158 Replaces Version: 1 / GB Print date: 07.08.19

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4. Reference to other sections

Information regarding Safe handling, see Section 7. Information regarding personal protective measures, see Section 8. Information regarding waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Avoid skin and eye contact. Avoid the inhalation of particulates and spray mist arising from the application of this mixture. Smoking, eating and drinking shall be prohibited in application area. For personal protection see Section 8. Never use pressure to empty: container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or water courses.

Advice on protection against fire and explosion

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

Classification of fires / temperature class / Ignition group / Dust explosion class

Classification of fires B (Combustible liquid substances)

Temperature class T2

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Electrical installations/working materials must comply with the local applied technological safety standards. Storage rooms in which filling operations take place must have a conducting floor. Store in accordance with national regulation

Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

Further information on storage conditions

Observe label precautions. Store between 15 and 30 °C in a dry, well ventilated place away from sources of heat and direct sunlight. Keep container tightly closed. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

7.3. Specific end use(s)

Paint

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limit values

Acetone

List EH40 Type WEL

Value $1210 \text{ mg/m}^3 500 \text{ ppm(V)}$

Trade name: Marabu Alcohol Ink 158, 20ml MNA

Version: 2 / GB Date revised: 17.07.2019

Substance number: 12169007158 Replaces Version: 1 / GB Print date: 07.08.19

Short term exposure limit 3620 mg/m³ 1500 ppm(V)

Status: 2011

Propan-2-ol

List EH40 Type WEL

Value 999 mg/m^3 400 ppm(V)Short term exposure limit 1250 mg/m^3 500 ppm(V)

Status: 2011

Derived No/Minimal Effect Levels (DNEL/DMEL)

Acetone

Type of value Derived No Effect Level (DNEL)

Reference group Worker

Duration of exposure Long term
Route of exposure dermal

Concentration 186 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Short term
Route of exposure inhalative
Concentration 2420

Concentration 2420 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Worker

Duration of exposure Long term

Route of exposure inhalative

Concentration 1210 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Duration of exposure Long term
Route of exposure oral

Concentration 62 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Duration of exposure Long term

Concentration 62 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group

Duration of exposure

Route of exposure

Concentration

Concentration 200 mg/m³

Propan-2-ol

Type of value Derived No Effect Level (DNEL)

Reference group

Duration of exposure

Route of exposure

Mode of action

Systemic effects

Concentration 500 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term

Trade name: Marabu Alcohol Ink 158, 20ml MNA

Version: 2 / GB Date revised: 17.07.2019

Substance number: 12169007158 Replaces Version: 1 / GB Print date: 07.08.19

Route of exposure dermal

Mode of action Systemic effects

Concentration 888 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group General Population

Duration of exposure
Route of exposure
Mode of action
Systemic effects

Concentration 89 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group General Population

Duration of exposure Long term Route of exposure dermal

Mode of action Systemic effects

Concentration 319 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group General Population

Duration of exposure Long term Route of exposure oral

Mode of action Systemic effects

Concentration 26 mg/kg/d

Predicted No Effect Concentration (PNEC)

Acetone

Type of value PNEC Freshwater

Concentration 10,6 mg/l

Type of value PNEC
Type Saltwater

Concentration 1,06 mg/l

Type of value PNEC

Type Water (intermittent release)

Concentration 21 mg/l

Type of value PNEC

Type Freshwater sediment

Concentration 30,4 mg/kg

Type of value PNEC

Type Marine sediment

Concentration 3,04 mg/kg

Type of value PNEC Type Soil

Concentration 29,5 mg/kg

Type of value PNEC

Type Sewage treatment plant (STP)

Concentration 100 mg/l

Propan-2-ol

Type of value PNEC

Trade name: Marabu Alcohol Ink 158, 20ml MNA

Version: 2 / GB Date revised: 17.07.2019

Substance number: 12169007158 Replaces Version: 1 / GB Print date: 07.08.19

Type Freshwater

Concentration 140,9 mg/l

Type of value PNEC
Type Saltwater

Concentration 140,9 mg/l

Type of value PNEC

Type Sewage treatment plant (STP)

Concentration 2251 mg/l

Type of value PNEC

Type Freshwater sediment

Concentration 552 mg/kg

Type of value PNEC

Type Marine sediment

Concentration 552 mg/kg

Type of value PNEC Type Soil

Concentration 28 mg/kg

8.2. Exposure controls

Exposure controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. Full mask, filter A

Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

For prolonged or repeated handling nitrile rubber gloves with textile undergloves are required.

Material thickness > 0,5 mm Breakthrough time < 30 min

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

Eve protection

Use safety eyewear designed to protect against splash of liquids.

Body protection

Cotton or cotton/synthetic overalls or coveralls are normally suitable.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Trade name: Marabu Alcohol Ink 158, 20ml MNA

Version: 2 / GB Date revised: 17.07.2019

Substance number: 12169007158 Replaces Version: 1 / GB Print date: 07.08.19

Form liquid Coloured

Odour solvent-like

Odour threshold

Remarks No data available

pH value

Remarks Not applicable

Melting point

Remarks not determined

Freezing point

Remarks not determined

Initial boiling point and boiling range

Value appr. 82 °C

Flash point

Value 20 °C

Evaporation rate (ether = 1):

Remarks not determined

Flammability (solid, gas)

Not applicable

Upper/lower flammability or explosive limits

Lower explosion limit appr. 2 %(V)
Upper explosion limit appr. 13 %(V)

Source Literature value

Vapour pressure

Value appr. 45 hPa

Vapour density

Remarks not determined

Density

Remarks not determined

Solubility in water

Remarks partially miscible

Partition coefficient: n-octanol/water

Remarks Not applicable

Ignition temperature

Value appr. 425 °C

Source Literature value

Viscosity

Value 150 to 250 mPa.s

Efflux time

Value < 12 s

Temperature 20 °C

Method DIN 53211 4 mm

Explosive properties

evaluation no

Oxidising properties

evaluation None known

9.2. Other information

Trade name: Marabu Alcohol Ink 158, 20ml MNA

Version: 2 / GB Date revised: 17.07.2019

Substance number: 12169007158 Replaces Version: 1 / GB Print date: 07.08.19

Other information

The physical specifications are approximate values and refer to the used safety relevant component(s).

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reactions when stored and handled according to prescribed instructions.

10.2. Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3. Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4. Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

10.5. Incompatible materials

No hazardous reactions when stored and handled according to prescribed instructions.

10.6. Hazardous decomposition products

See chapter 5.2 (Firefighting measures - Special hazards arising from the substance or mixture).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute oral toxicity

Remarks Based on available data, the classification criteria are not met.

Acute oral toxicity (Components)

Acetone

Species rat

LD50 5800 mg/kg

Acute dermal toxicity (Components)

Acetone

Species rabbit

LD50 20000 mg/kg

Acute inhalational toxicity

Remarks Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Remarks Based on available data, the classification criteria are not met.

Serious eye damage/irritation

evaluation irritant

Remarks The classification criteria are met.

Sensitization

Remarks Based on available data, the classification criteria are not met.

Mutagenicity

Remarks Based on available data, the classification criteria are not met.

Reproductive toxicity

Remarks Based on available data, the classification criteria are not met.

Carcinogenicity

Remarks Based on available data, the classification criteria are not met.

Trade name: Marabu Alcohol Ink 158, 20ml MNA

Version: 2 / GB Date revised: 17.07.2019

Substance number: 12169007158 Replaces Version: 1 / GB Print date: 07.08.19

Specific Target Organ Toxicity (STOT)

Single exposure

Remarks The classification criteria are met. evaluation May cause drowsiness or dizziness.

Repeated exposure

Remarks Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Experience in practice

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Other information

There are no data available on the mixture itself.

The mixture has been assessed following the additivity method of the GHS/CLP Regulation (EC) No 1272/2008.

SECTION 12: Ecological information

12.1. Toxicity

General information

There are no data available on the mixture itself.Do not allow to enter drains or water courses.The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as dangerous for the environment.

12.2. Persistence and degradability

General information

No data available

12.3. Bioaccumulative potential

General information

There are no data available on the mixture itself.

Partition coefficient: n-octanol/water

Remarks Not applicable

12.4. Mobility in soil

General information

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

General information

There are no data available on the mixture itself.

12.6. Other adverse effects

General information

Trade name: Marabu Alcohol Ink 158, 20ml MNA

Version: 2 / GB Date revised: 17.07.2019

Substance number: 12169007158 Replaces Version: 1 / GB Print date: 07.08.19

There are no data available on the mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations for the product

Do not allow to enter drains or water courses.

Wastes and emptied containers should be classified in accordance with relevant national regulation.

The European Waste Catalogue classification of this product, when disposed of as waste is EWC waste code 08 03 12* waste ink containing dangerous substances

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

For further information contact your local waste authority.

Disposal recommendations for packaging

Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Not emptied containers are hazardous waste (waste code number 150110).

SECTION 14: Transport information

Land transport ADR/RID

14.1. UN number

UN 1263

14.2. UN proper shipping name

PAINT

14.3. Transport hazard class(es)

Class 3 Label 3

14.4. Packing group

Packing group II
Special provision 640D
Limited Quantity 5 I
Transport category 3

14.5. Environmental hazards

Tunnel restriction code D/E

Marine transport IMDG/GGVSee

14.1. UN number

UN 1263

14.2. UN proper shipping name

PAINT

14.3. Transport hazard class(es)

Class

14.4. Packing group

Packing group

14.5. Environmental hazards

no

Air transport ICAO/IATA

14.1. UN number

UN 1263

14.2. UN proper shipping name

PAINT

14.3. Transport hazard class(es)

Class 3

Trade name: Marabu Alcohol Ink 158, 20ml MNA

Version: 2 / GB Date revised: 17.07.2019

Substance number: 12169007158 Replaces Version: 1 / GB Print date: 07.08.19

14.4. Packing group

Packing group II

14.5. Environmental hazards

-

Information for all modes of transport

14.6. Special precautions for user

Transport within the user's premises:

Always transport in closed containers that are upright and secure.

Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Other information

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

nc

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Major-accident categories acc. 96/82/EC

Category 7B Highly flammable liquids 5.000.000 kg 50.000.000 kg

Other information

The product does not contain substances of very high concern (SVHC).

15.2. Chemical safety assessment

For this preparation a chemical safety assessment has not been carried out.

SECTION 16: Other information

Hazard statements listed in Chapter 3

H225 Highly flammable liquid and vapour.
 H312 Harmful in contact with skin.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

CLP categories listed in Chapter 3

Acute Tox. 4 Acute toxicity, Category 4
Eye Irrit. 2 Eye irritation, Category 2
Flam. Liq. 2 Flammable liquid, Category 2

STOT SE 3 Specific target organ toxicity - single exposure, Category 3

Supplemental information

Relevant changes compared with the previous version of the safety data sheet are marked with: *** This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship. The information in this Safety Data Sheet is based on the present state of knowledge and current legislation.

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions.

As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.