



Trade name: Marabu easy marble 039, 15 ml MNA

Version: 12 / GB

Date revised: 11.07.2019

Substance number: 13059039039

Replaces Version: 11 / GB

Print date: 20.07.19

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Marabu easy marble 039, 15 ml MNA

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/preparation

Paint

Identified Uses

SU21

Consumer uses: Private households (= general public = consumers)

PC9a

Coatings and paints, thinners, paint removers

1.3. Details of the supplier of the safety data sheet

Address

Marabu GmbH & Co. KG

Asperger Strasse 4

71732 Tamm

Germany

Telephone no.

+49-7141/691-0

Fax no.

+49-7141/691-147

Information provided

Department product safety

by / telephone

E-mail address of

PRSI@marabu.de

person responsible

for this SDS

1.4. Emergency telephone number

(+49) (0)621-60-43333

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3

H226

STOT SE 3

H336

2.2. Label elements

Labelling according to regulation (EC) No 1272/2008

Hazard pictograms



Signal word

Warning

Hazard statements

H226

Flammable liquid and vapour.

H336

May cause drowsiness or dizziness.

Precautionary statements



Trade name: Marabu easy marble 039, 15 ml MNA

Version: 12 / GB

Date revised: 11.07.2019

Substance number: 13059039039

Replaces Version: 11 / GB

Print date: 20.07.19

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P405	Store locked up.
P501.9	Dispose of contents/container as problematic waste.

Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

contains 1-Methoxy-2-propanol;Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics;2-Methoxy-1-methylethyl acetate

2.3. Other hazards

No special hazards have to be mentioned.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

Paint based on alkyd resins and on solvents

Hazardous ingredients**1-Methoxy-2-propanol**

CAS No.	107-98-2
EINECS no.	203-539-1
Registration no.	01-2119457435-35
Concentration	>= 25 < 50 %

Classification (Regulation (EC) No. 1272/2008)

STOT SE 3	H336
Flam. Liq. 3	H226

2-Methoxy-1-methylethyl acetate

CAS No.	108-65-6
EINECS no.	203-603-9
Registration no.	01-2119475791-29
Concentration	>= 10 < 20 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3	H226
STOT SE 3	H336

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

CAS No.	64742-48-9
EINECS no.	265-150-3
Registration no.	01-2119463258-33 (LIST NUMBER 919-857-5)
Concentration	>= 10 < 20 %

Classification (Regulation (EC) No. 1272/2008)

Asp. Tox. 1	H304
Flam. Liq. 3	H226
STOT SE 3	H336
	EUH066

2-Butoxyethyl acetate

CAS No.	112-07-2
EINECS no.	203-933-3



Trade name: Marabu easy marble 039, 15 ml MNA

Version: 12 / GB

Date revised: 11.07.2019

Substance number: 13059039039

Replaces Version: 11 / GB

Print date: 20.07.19

Registration no. 01-2119475112-47
 Concentration >= 1 < 10 %

Classification (Regulation (EC) No. 1272/2008)
 Acute Tox. 4 H332
 Acute Tox. 4 H312
 Acute Tox. 4 H302

2-Methoxypropanol

CAS No. 1589-47-5
 EINECS no. 216-455-5
 Concentration >= 0,1 < 0,3 %

Classification (Regulation (EC) No. 1272/2008)
 Skin Irrit. 2 H315
 STOT SE 3 H335
 Repr. 1B H360D
 Flam. Liq. 3 H226
 Eye Dam. 1 H318

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Until now no symptoms known so far.

4.3. Indication of any immediate medical attention and special treatment needed**Hints for the physician / treatment**

Treat symptomatically

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Recommended: alcohol resistant foam, CO₂, powders, water spray/mist, Not be used for safety reasons: water jet



Trade name: Marabu easy marble 039, 15 ml MNA

Version: 12 / GB

Date revised: 11.07.2019

Substance number: 13059039039

Replaces Version: 11 / GB

Print date: 20.07.19

5.2. Special hazards arising from the substance or mixture

In the event of fire the following can be released: Carbon monoxide (CO); Carbon dioxide (CO₂); dense black smoke; Nitrogen oxides (NO_x)

5.3. Advice for firefighters

Special protective equipment for fire-fighting

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Do not allow to enter drains or waterways. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4. Reference to other sections

Information regarding Safe handling, see Section 7. Information regarding personal protective measures, see Section 8. Information regarding waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Avoid skin and eye contact. Avoid the inhalation of particulates and spray mist arising from the application of this mixture. Smoking, eating and drinking shall be prohibited in application area. For personal protection see Section 8. Never use pressure to empty: container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or water courses.

Advice on protection against fire and explosion

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

Classification of fires / temperature class / Ignition group / Dust explosion class

Classification of fires	B (Combustible liquid substances)
Temperature class	T4

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Electrical installations/working materials must comply with the local applied technological safety standards. Storage rooms in which filling operations take place must have a conducting floor. Store in accordance with national regulation



Trade name: Marabu easy marble 039, 15 ml MNA

Version: 12 / GB

Date revised: 11.07.2019

Substance number: 13059039039

Replaces Version: 11 / GB

Print date: 20.07.19

Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

Further information on storage conditions

Observe label precautions. Store between 15 and 30 °C in a dry, well ventilated place away from sources of heat and direct sunlight. Keep container tightly closed. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

7.3. Specific end use(s)

Paint

SECTION 8: Exposure controls/personal protection *****8.1. Control parameters****Exposure limit values *******2-Methoxy-1-methylethyl acetate**

List	EH40			
Type	WEL			
Value	274	mg/m ³	50	ppm(V)
Short term exposure limit	548	mg/m ³	100	ppm(V)
Skin resorption / sensibilisation: Sk; Status: 2011				

1-Methoxy-2-propanol

List	EH40			
Type	WEL			
Value	375	mg/m ³	100	ppm(V)
Short term exposure limit	560	mg/m ³	150	ppm(V)
Skin resorption / sensibilisation: Sk; Status: 2011				

2-Butoxyethyl acetate

List	EH40			
Type	WEL			
Value	133		20	ppm(V)
Short term exposure limit	332		50	ppm(V)
Skin resorption / sensibilisation: Sk; Status: 2011				

Derived No/Minimal Effect Levels (DNEL/DMEL) *****2-Methoxy-1-methylethyl acetate**

Type of value	Derived No Effect Level (DNEL)			
Reference group	Worker			
Duration of exposure	Long term			
Route of exposure	dermal			
Mode of action	Systemic effects			
Concentration	796			mg/kg/d

Type of value	Derived No Effect Level (DNEL)			
Reference group	Worker			
Duration of exposure	Long term			
Route of exposure	inhalative			
Mode of action	Systemic effects			
Concentration	275			mg/m ³

Type of value	Derived No Effect Level (DNEL)			
Reference group	Consumer			
Duration of exposure	Long term			
Route of exposure	dermal			
Mode of action	Systemic effects			
Concentration	320			mg/kg/d

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Marabu easy marble 039, 15 ml MNA

Version: 12 / GB

Date revised: 11.07.2019

Substance number: 13059039039

Replaces Version: 11 / GB

Print date: 20.07.19

Type of value Derived No Effect Level (DNEL)
 Reference group Consumer
 Duration of exposure Long term
 Route of exposure inhalative
 Mode of action Systemic effects
 Concentration 33 mg/m³

Type of value Derived No Effect Level (DNEL)
 Reference group Consumer
 Duration of exposure Long term
 Route of exposure inhalative
 Mode of action Local effects
 Concentration 33 mg/m³

Type of value Derived No Effect Level (DNEL)
 Reference group Consumer
 Duration of exposure Long term
 Route of exposure oral
 Mode of action Systemic effects
 Concentration 36 mg/kg/d

Type of value Derived No Effect Level (DNEL)
 Reference group Worker
 Duration of exposure Lifetime
 Route of exposure inhalative
 Mode of action Local effects
 Concentration 550 mg/m³

2-Butoxyethyl acetate

Reference substance 2-Butoxyethyl acetate
 Type of value Derived No Effect Level (DNEL)
 Reference group Worker
 Duration of exposure Long term
 Route of exposure inhalative
 Mode of action Systemic effects
 Concentration 133 mg/m³

Type of value 2-Butoxyethyl acetate
 Derived No Effect Level (DNEL)
 Reference group Worker
 Duration of exposure Short term
 Route of exposure inhalative
 Mode of action Local effects
 Concentration 333 mg/m³

Type of value 2-Butoxyethyl acetate
 Derived No Effect Level (DNEL)
 Reference group Worker
 Duration of exposure Long term
 Route of exposure dermal
 Mode of action Systemic effects
 Concentration 169 mg/kg/d

Type of value 2-Butoxyethyl acetate
 Derived No Effect Level (DNEL)
 Reference group Worker

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Marabu easy marble 039, 15 ml MNA

Version: 12 / GB

Date revised: 11.07.2019

Substance number: 13059039039

Replaces Version: 11 / GB

Print date: 20.07.19

Duration of exposure Short term
 Route of exposure dermal
 Mode of action Systemic effects
 Concentration 120 mg/kg/d

Type of value 2-Butoxyethyl acetate
 Reference group Derived No Effect Level (DNEL)
 Duration of exposure Long term
 Route of exposure inhalative
 Mode of action Systemic effects
 Concentration 80 mg/m³

Type of value 2-Butoxyethyl acetate
 Reference group Derived No Effect Level (DNEL)
 Duration of exposure Short term
 Route of exposure inhalative
 Mode of action Local effects
 Concentration 200 mg/m³

Type of value 2-Butoxyethyl acetate
 Reference group Derived No Effect Level (DNEL)
 Duration of exposure Long term
 Route of exposure dermal
 Mode of action Systemic effects
 Concentration 102 mg/kg/d

Type of value 2-Butoxyethyl acetate
 Reference group Derived No Effect Level (DNEL)
 Duration of exposure Short term
 Route of exposure dermal
 Mode of action Systemic effects
 Concentration 72 mg/kg/d

Type of value 2-Butoxyethyl acetate
 Reference group Derived No Effect Level (DNEL)
 Duration of exposure Long term
 Route of exposure oral
 Mode of action Systemic effects
 Concentration 8,6 mg/kg/d

Type of value 2-Butoxyethyl acetate
 Reference group Derived No Effect Level (DNEL)
 Duration of exposure Short term
 Route of exposure oral
 Mode of action Systemic effects
 Concentration 36 mg/kg/d

1-Methoxy-2-propanol

Type of value Derived No Effect Level (DNEL)
 Reference group Worker
 Duration of exposure Acute

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Marabu easy marble 039, 15 ml MNA

Version: 12 / GB

Date revised: 11.07.2019

Substance number: 13059039039

Replaces Version: 11 / GB

Print date: 20.07.19

Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	553,5	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	50,6	mg/person/ d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	369	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	General Population	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	18,1	mg/kg
Type of value	Derived No Effect Level (DNEL)	
Reference group	General Population	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	43,9	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	General Population	
Duration of exposure	Long term	
Route of exposure	oral	
Mode of action	Systemic effects	
Concentration	3,3	mg/kg/d

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	300	mg/kg
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	oral	
Mode of action	Systemic effects	
Concentration	300	mg/kg
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Marabu easy marble 039, 15 ml MNA

Version: 12 / GB

Date revised: 11.07.2019

Substance number: 13059039039

Replaces Version: 11 / GB

Print date: 20.07.19

Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	300	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	900	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	1500	mg/m ³

Predicted No Effect Concentration (PNEC)

2-Methoxy-1-methylethyl acetate

Reference substance	2-Methoxy-1-methylethyl acetate	
Type of value	PNEC	
Type	Freshwater	
Concentration	0,635	mg/l

Type of value	PNEC	
Type	Freshwater sediment	
Concentration	3,29	mg/kg

Type of value	PNEC	
Type	Soil	
Concentration	0,29	mg/kg
Source	Literature value	

Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	100	mg/l
Source	Literature value	

Type of value	PNEC	
Type	Marine sediment	
Concentration	0,329	mg/kg
Source	Literature value	

Type of value	PNEC	
Type	Saltwater	
Concentration	0,0635	mg/l

2-Butoxyethyl acetate

Reference substance	2-Butoxyethyl acetate	
Type of value	PNEC	
Type	Water	
Concentration	0,304	mg/l
Source	Literature value	

2-Butoxyethyl acetate



Trade name: Marabu easy marble 039, 15 ml MNA

Version: 12 / GB

Date revised: 11.07.2019

Substance number: 13059039039

Replaces Version: 11 / GB

Print date: 20.07.19

Type of value	PNEC		
Type	Aquatic		
Concentration	0,0304		g/l
Source	Literature value		
Type of value	2-Butoxyethyl acetate		
Type	PNEC		
Concentration	2,03		mg/kg
Source	Literature value		
Type of value	2-Butoxyethyl acetate		
Type	PNEC		
Concentration	0,203		mg/kg
Source	Literature value		
Type of value	2-Butoxyethyl acetate		
Type	PNEC		
Concentration	0,203		mg/kg
Source	Literature value		
Type of value	2-Butoxyethyl acetate		
Type	PNEC		
Concentration	0,68		mg/kg
Source	Literature value		
1-Methoxy-2-propanol			
Type of value	PNEC		
Type	Freshwater		
Concentration	10		mg/l
Type of value	PNEC		
Type	Water		
Concentration	41,6		mg/kg
Type of value	PNEC		
Type	Sediment		
Concentration	41,6		mg/kg
Type of value	PNEC		
Type	Marine sediment		
Concentration	4,17		mg/kg
Type of value	PNEC		
Type	Soil		
Concentration	2,47		mg/kg
Type of value	PNEC		
Type	Sewage treatment plant (STP)		
Concentration	100		mg/l

8.2. Exposure controls

Exposure controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. Full mask, filter A



Trade name: Marabu easy marble 039, 15 ml MNA

Version: 12 / GB

Date revised: 11.07.2019

Substance number: 13059039039

Replaces Version: 11 / GB

Print date: 20.07.19

Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

For prolonged or repeated handling nitrile rubber gloves with textile undergloves are required.

Material thickness > 0,5 mm

Breakthrough time < 30 min

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

Eye protection

Use safety eyewear designed to protect against splash of liquids.

Body protection

Cotton or cotton/synthetic overalls or coveralls are normally suitable.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Form	liquid		
Colour	coloured		
Odour	solvent-like		
Odour threshold			
Remarks	No data available		
pH value			
Remarks	Not applicable		
Melting point			
Remarks	not determined		
Freezing point			
Remarks	not determined		
Initial boiling point and boiling range			
Value	appr. 120		°C
Pressure	1.013	hPa	
Source	Literature value		
Flash point			
Value	30		°C
Method	ASTM D 6450 (CCCFP)		
Evaporation rate (ether = 1) :			
Remarks	not determined		
Flammability (solid, gas)			
Not applicable			
Upper/lower flammability or explosive limits			
Lower explosion limit	appr. 0,7		%(V)
Upper explosion limit	appr. 13,7		%(V)
Source	Literature value		
Vapour pressure			



Trade name: Marabu easy marble 039, 15 ml MNA

Version: 12 / GB

Date revised: 11.07.2019

Substance number: 13059039039

Replaces Version: 11 / GB

Print date: 20.07.19

Value	8			hPa
Temperature	20	°C		
Method	calculated			

Vapour density

Remarks: not determined

Density

Value	0,96			g/cm ³
Temperature	20	°C		
Method	DIN EN ISO 2811			

Solubility in water

Remarks: partially miscible

Partition coefficient: n-octanol/water

Remarks: Not applicable

Ignition temperature

Value	appr. 200			°C
Source	Literature value			

Viscosity**dynamic**

Value	30	to	50	mPa.s
Temperature	40	°C		

Efflux time

Value	25	to	70	s
Temperature	20	°C		
Method	DIN 53211 4 mm			

Explosive properties

evaluation: no

Oxidising properties

evaluation: None known

9.2. Other information**Other information**

The physical specifications are approximate values and refer to the used safety relevant component(s).

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reactions when stored and handled according to prescribed instructions.

10.2. Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3. Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4. Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

10.5. Incompatible materials

No hazardous reactions when stored and handled according to prescribed instructions.

10.6. Hazardous decomposition products

See chapter 5.2 (Firefighting measures - Special hazards arising from the substance or mixture).



Trade name: Marabu easy marble 039, 15 ml MNA

Version: 12 / GB

Date revised: 11.07.2019

Substance number: 13059039039

Replaces Version: 11 / GB

Print date: 20.07.19

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute oral toxicity (Components)

1-Methoxy-2-propanol

Species	rat		
LD50		5200	mg/kg

Acute dermal toxicity (Components)

1-Methoxy-2-propanol

Species	rabbit		
LD50		14000	mg/kg

Acute inhalational toxicity

Remarks	Based on available data, the classification criteria are not met.
---------	---

Skin corrosion/irritation

Remarks	Based on available data, the classification criteria are not met.
---------	---

Serious eye damage/irritation

Remarks	Based on available data, the classification criteria are not met.
---------	---

Sensitization

Remarks	Based on available data, the classification criteria are not met.
---------	---

Mutagenicity

Remarks	Based on available data, the classification criteria are not met.
---------	---

Reproductive toxicity

Remarks	Based on available data, the classification criteria are not met.
---------	---

Carcinogenicity

Remarks	Based on available data, the classification criteria are not met.
---------	---

Specific Target Organ Toxicity (STOT)

Single exposure

Remarks	The classification criteria are met.
evaluation	May cause drowsiness or dizziness.

Repeated exposure

Remarks	Based on available data, the classification criteria are not met.
---------	---

Aspiration hazard

Remarks	Based on available data, the classification criteria are not met.
---------	---

Experience in practice

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Other information

There are no data available on the mixture itself.

The mixture has been assessed following the additivity method of the GHS/CLP Regulation (EC) No 1272/2008.



Trade name: Marabu easy marble 039, 15 ml MNA

Version: 12 / GB

Date revised: 11.07.2019

Substance number: 13059039039

Replaces Version: 11 / GB

Print date: 20.07.19

SECTION 12: Ecological information

12.1. Toxicity

General information

There are no data available on the mixture itself. Do not allow to enter drains or water courses. The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as dangerous for the environment.

Fish toxicity (Components)

1-Methoxy-2-propanol

Species	golden orfe (Leuciscus idus)		
LC0	>	4600	mg/l
Duration of exposure		96	h

Daphnia toxicity (Components)

1-Methoxy-2-propanol

Species	Daphnia magna		
EC50		23300	mg/l
Duration of exposure		48	h

Algae toxicity (Components)

1-Methoxy-2-propanol

Species	Desmodesmus		
EC50	>	1000	mg/l
Duration of exposure		168	h

Bacteria toxicity (Components)

1-Methoxy-2-propanol

Species	activated sludge		
EC50	>	1000	mg/l

12.2. Persistence and degradability

General information

No data available

Biodegradability (Components)

1-Methoxy-2-propanol

Value	90		%
Duration of test evaluation	28		d
Method	Readily biodegradable (according to OECD criteria) OECD 301 F		

12.3. Bioaccumulative potential

General information

There are no data available on the mixture itself.

Partition coefficient: n-octanol/water

Remarks Not applicable

12.4. Mobility in soil

General information

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

General information

There are no data available on the mixture itself.



Trade name: Marabu easy marble 039, 15 ml MNA

Version: 12 / GB

Date revised: 11.07.2019

Substance number: 13059039039

Replaces Version: 11 / GB

Print date: 20.07.19

12.6. Other adverse effects

General information

There are no data available on the mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations for the product

Do not allow to enter drains or water courses.

Wastes and emptied containers should be classified in accordance with relevant national regulation.

The European Waste Catalogue classification of this product, when disposed of as waste is

EWC waste code 08 01 11* waste paint and varnish containing organic solvents or other dangerous substances

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

For further information contact your local waste authority.

Disposal recommendations for packaging

Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Not emptied containers are hazardous waste (waste code number 150110).

SECTION 14: Transport information

Land transport ADR/RID

14.1. UN number

UN 1263

14.2. UN proper shipping name

PAINT

14.3. Transport hazard class(es)

Class 3

Label 3

14.4. Packing group

Packing group III

Special provision 640E

Limited Quantity 5 I

Transport category 3

14.5. Environmental hazards

-

Tunnel restriction code D/E

Marine transport IMDG/GGVSee

14.1. UN number

UN 1263

14.2. UN proper shipping name

PAINT

14.3. Transport hazard class(es)

Class 3

14.4. Packing group

Packing group III

14.5. Environmental hazards

no

Air transport ICAO/IATA

14.1. UN number

UN 1263



Trade name: Marabu easy marble 039, 15 ml MNA

Version: 12 / GB

Date revised: 11.07.2019

Substance number: 13059039039

Replaces Version: 11 / GB

Print date: 20.07.19

14.2. UN proper shipping name

PAINT

14.3. Transport hazard class(es)

Class 3

14.4. Packing group

Packing group III

14.5. Environmental hazards

-

Information for all modes of transport**14.6. Special precautions for user**

Transport within the user's premises:

Always transport in closed containers that are upright and secure.

Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Other information**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

no

SECTION 15: Regulatory information *****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Major-accident categories acc. 96/82/EC**

Category	6	Flammable	5.000.000	kg	50.000.000	kg
----------	---	-----------	-----------	----	------------	----

VOC ***

VOC (EU)	76,36	%
VOC (EU)	733,1	g/l

Other information ***

The product does not contain substances of very high concern (SVHC).

Other information

All components are contained in the AICS inventory.

All components are contained in the DSL inventory.

All components are contained in the ENCS inventory.

All components are contained in the TSCA inventory or exempted.

15.2. Chemical safety assessment

For this preparation a chemical safety assessment has not been carried out.

SECTION 16: Other information**Hazard statements listed in Chapter 3**

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H360D	May damage the unborn child.

CLP categories listed in Chapter 3

Acute Tox. 4	Acute toxicity, Category 4
--------------	----------------------------

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Marabu easy marble 039, 15 ml MNA

Version: 12 / GB

Date revised: 11.07.2019

Substance number: 13059039039

Replaces Version: 11 / GB

Print date: 20.07.19

Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage, Category 1
Flam. Liq. 3	Flammable liquid, Category 3
Repr. 1B	Reproductive toxicity, Category 1B
Skin Irrit. 2	Skin irritation, Category 2
STOT SE 3	Specific target organ toxicity - single exposure, Category 3

Supplemental information

Relevant changes compared with the previous version of the safety data sheet are marked with: ***
This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.
The information in this Safety Data Sheet is based on the present state of knowledge and current legislation.

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions.

As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.